

# MATERIAL SAFETY DATA SHEET

ISSUE DATE: 8/21/01

REVISED DATE: 10/23/09

Supersedes: Any Previous M.S.D.S. On This Product

EMERGENCY PHONE NUMBER: CHEM-TEL INC. 1-800-255-3924

## I. IDENTIFICATION

**PRODUCT NAME:** Quicksleeve EPDM Gasket

**CHEMICAL NAME:** Synthetic Closed Cell Sponge Rubber

**CHEMICAL FAMILY:** Elastomeric Sponge

**PRODUCT CLASS:** Polymer

**PRODUCT DESCRIPTION:** Chemically Expanded Polymers

DUCTMATE INDUSTRIES, INC.

210 5<sup>th</sup> St.

Charleroi, PA 15022

## II. HAZARDOUS INGREDIENTS

| <u>MATERIAL:</u> | <u>CAS NUMBER</u> | <u>WEIGHT</u> | <u>OSHA</u><br><u>PEL</u> | <u>ACGIH</u><br><u>TLV</u> |
|------------------|-------------------|---------------|---------------------------|----------------------------|
| Zinc Compounds   | N/A               | <3.6%         |                           |                            |

The composition of this mixture may be considered proprietary information. In the event of a medical emergency, compositional information will be provided to a physician or nurse.

## III. PHYSICAL DATA

**APPEARANCE:**

**SOLUBILITY IN WATER:** Insoluble

**SPECIFIC GRAVITY:** .048-.449

**EVAPORATION RATE:** N/A

## IV. HEALTH HAZARD DATA

**INHALATION:** No hazard expected at ambient temperature.

**SKIN CONTACT:** No hazard expected in normal industrial use.

**EYE CONTACT:** Particulates may cause eye irritation.

**INGESTION:** Not expected in normal industrial use.

## V. EMERGENCY AND FIRST AID PROCEDURES

**INHALATION:** N/A

**SKIN CONTACT:** Wash with soap and water.

**EYE CONTACT:** Flush with water five minutes, contact physician if irritation persists.

**INGESTION:** Contact a physician.

## VI. FIRE AND EXPLOSION HAZARD DATA

**FLASH POINT:** 415° F (Approximately)

**EXTINGUISHING MEDIA:** Water Fog, ABC Dry Chemical

**SPECIAL PROCEDURES:** This material will burn. In case of fire wear self-contained breathing apparatus to prevent inhalation of toxic combustion gases.

**HAZARDOUS COMBUSTION PRODUCTS:** Carbon monoxide, Carbon dioxide.

## VII. SPILL OR LEAK PROCEDURES

**SPILL PROCEDURE:** Apply normal clean-up procedures and store for re-use or disposal.

**WASTE DISPOSAL:** Dispose of in accordance with all Federal, State and Local regulations. Contact local environmental authorities for approved disposal of this material.

## VIII. SPECIAL PROTECTION

**VENTILATION:** General exhaust recommended.

**PERSONAL PROTECTION:** Safety goggles and an OSHA approved particulate respirator are recommended for cutting, grinding, and sawing operations.

**OTHER PRECAUTIONS:** Practice good industrial hygiene.

## **IX. REACTIVITY DATA**

**STABILITY:** Stable.

**CONDITIONS TO AVOID:** Do not use or store near or flame.

**INCOMPATIBILITY/MATERIALS TO AVOID:** None known.

**HAZARDOUS DECOMPOSITION PRODUCT:** If burned: Smoke, soot and toxic fumes, including carbon monoxide and carbon dioxide.

**HAZARDOUS POLYMERIZATION:** Will not occur.

## **X. SPECIAL PRECAUTIONS**

**STORAGE TEMPERATURE:** Ambient

**STORAGE / TRANSPORT PRESSURE:** Atmospheric

**SPECIAL PRECAUTIONS FOR HANDLING AND STORAGE:** None

This information is taken from sources or based upon data believed to be reliable; however, DUCTMATE INDUSTRIES, INC. makes no warranty as to the absolute correctness or sufficiency of any of the foregoing or that additional or other measures may not be required under particular conditions.